



TYPE 42 BLUEstream

Man. Hydraulic

FOIL Position	Average lift force reduction	Average drag force reduction
100% (full open)	0%	0%
75%	8%	8%
50%	16%	16%
25%	23%	22%
0% (full closed)	27%	25%



TIPS

Open only upper flaps. Upper part surface is reduced. Door will lean inward.

Open only lower flaps. Lower part surface is reduced. Door will lean outward.

Open equal flaps for upper and lower part. Same surface reduce for whole door. Door will keep position (only surface reduced / less door to door distance).

Size m²	Standard weight/kg	Max Weight
2,0	350	As request
2,25	390	As request
2,5	420	As request
2,75	450	As request
3,0	640	As request
3,25	690	As request
3,5	740	As request
3,75	790	As request
4,0	840	As request
4,5	980	As request
5,0	1080	As request
5,5	1350	As request
6,0	1500	As request
6,5	1670	As request
7,0	2140	As request
7,5	2200	As request
8,0	2350	As request
8,5	2490	As request
9,0	2640	As request
9,5	2780	As request
10,0	2900	As request
10,5	3030	As request
11,0	3180	As request
11,5	3320	As request
12,0	3450	As request
12,5	3600	As request
13,0	3780	As request
13,5	3920	As request
14,0	4050	As request
14,5	4200	As request
15,0	4320	As request
15,5	4460	As request
16,0	4620	As request

Special weights on request

Thyboron Trawldoor is certified to use high quality steel materials





